



1. Product and Company Identifica	tion			
Brand name Product name	ProFormance [®] ProFormance [®] Premier Casting Tape			
General chemical characteristics	Isocyanate terminated polyurethane resin			
Analysis of noxiousness	Chronic exposure & contact may cause noxiousness			
Usage	Designed for applying pressure on, fixing, and giving support to specific areas of the body suffering complete or simple (twists, sprains, or impaired ligaments) fractures			
Supplier	BL Tech Co., Ltd. 84, Toegyenonggong-ro, Chuncheon-si, Gangwon-do, Korea(Rep.)			
Emergency phone number	Tel:+82-70-7449-7505, Fax:+82-31-629-5216 Tel:+82-70-7449-7505			
Issuing date	2006. 09. 06			
Revision number and date	Revision number:08 Date:2023.10.04			
2. Hazards Identification				
GHS classification				
. Health	1			
. Fire	1			
. Reactivity	0			
Symbols	الله الله الله الله الله الله الله الله			
Signal words	Warning			
Hazard Risk Statement	H315 Cause skin irritation			
	H317 May cause an allergic skin reaction			
	H319 Causes serious eye irritation			
	H332 Harmful if inhaled			
	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled			
	H335 May cause respiratory irritation			
	H373 May cause damage to organs through prolonged or repeated exposure			
Precautionary Statement	P201 Obtain special instruction before use			
	P202 Do not handle until all precautions have been read and understood.			
. Prevention	P262 Do not get in eyes, on skin, or on clothing.			
. Response	P301+P310 IF SWALLOWED : immediately call a POSION CENTER or doctor/physician			
	P302+P350 IF ON SKIN : Gently wash with plenty of soap and water			
	P305+P351+P338 IF IN EYES : Rinse cautiously with water for several minute. Remove contact lenses, if present and eyes to do. Continue rinsing.			
	P332+P313 If skin irritation or rash occur : Get medical advice/attention.			
	P337+P313 If eye irritation persists : Get medical advice/attention.			
. Storage	P402 Store in a dry place.			
	P403 Store in a well-ventilated place.			
	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F			
. Disposal	P501 Dispose of contents/container to in accordance with local/national regulation			





3. Composition/Information on Ingredients

	Product name		Name	Cas no			
	ProFormance®		Fiberglass fabric	65997-17-3			
	Premier Casting Tape		Polyisocyanation prepolymer Bastd on MDI [(1-Methyl-1,2-ethanediyl) bis(oxy)]bispropanol polymer with 1,1'-methylenebis[isocyanatobenzene]	103837-35-0			
			Colouration	N/A			
4. First Aid I	4. First Aid Measures						
Eye contact		Wash eyes immediately with large amounts of water or normal saline, until no evidence of chemical remains. (at least 15–20 minutes) get medical attention immediately.					
Skin contact		Remove contaminated clothing and shoes immediately. If skin is intact gently remove excess polymer, and immediately flush with undiluted isopropyl alcohol, then with large amount of water. If the skin is irritated, use diluted isopropyl alcohol.					
Inhalation		Perform artificial respiration if necessary. Keep person warn and at rest. Treat symptomatically and supportively.					
Ingestion		If vomiting occurs, keep head lower than hips to help. Prevent aspiration. Treat symptomatically and supportively. Get medical attention if needed.					
Note to physician		No specific antidote. Treat symptomatically and supportively.					
5. Fire-Fighting Measures							
Flash point		Over than 200°C					
Autoignition		No data available					
Lower/upper flammable limit		No data available					
Framable class		Osha : III b					
Extinguishing media		Dry chemical, carbon dioxide, water spray or regular foam for Larger fires, use water spray, fog, or regular foam.					
Fire fighting		Use agents suitable for type of surrounding fire. Avoid breathing hazardous vapors, keep upwind.					
Hazardous combustion products		Thermal decomposition products may include highly toxic fumes of hydrogen cyanide, toxic oxide of carbon and nitrogen, and Hazardous isocyanates.					
6. Accidenta	al Release Measures						
Necessary points to protect human body		Keep unnecessary people away: Isolate hazard area and restrict entry.					
Necessary p	Necessary points to protect ecology		Take up with sand or other absorbent material and place into containers for later disposal.				
Defecation or remove		An decontamination solution is a mixture containing 20parts, isopropyl alcohol, 40parts concentrated ammonia, 2-5 parts Household type detergent plus water to make 100 parts					
		Soil sp	ill: use cement powder or fly ash to absorb liquid	mass			
7. Handling and storage							
Handling		Observe all federal, state and local regulations when storing this substance.					
		Store away from incompatible substances.					
Storage		Keep container closed when not use and store in cool dry area.					





8. Exposure Controls and Personal P	rotection
Engineering control	No information is available
Respiration protection	Self-contained breathing apparatus. Air purifying, full face piece respirator. (gas mask) Supplied-air respirator.
Eye protection	Safety goggles
Hand protection	Appropriate protective gloves.
Body protection	Appropriate protective (impervious) clothing and equipment.
Cautions	Provide local exhaust or general dilution ventilation to meet published exposure limits.
Max. Concentration	No data available
9. Physical and Chemical Properties	
Appearance	Light yellow liquid
Odor	A characteristic odor
PH	No data available
Water solubility	React
Boiling point	No data available
Melting point	Over than 10°C
Explosion	No data available
Oxidative	No data available
Vapor pressure	No data available
Specific gravity	1.12 (25°C)
Distribution	No data available
Vapor density	No data available
Viscosity	15,000±5,000(cps/30±1°C)
10. Stability and Reactivity	
Chemical stability	Stable under normal temperatures and pressures.
Conditions to avoid	May burn but does not ignite readily. Avoid contact with strong oxidizers, excessive heat, sparks, or open flame.
Substances to avoid	Oxidizers (strong): fire and explosion hazard.
Hazardous decomposition	Thermal decomposition products may include highly toxic fumes of hydrogen toxic oxides of carbon and nitrogen, and hazardous isocyanate.
Polymerization	Hazardous polymerization has not been reported to occur under normal temperatures and pressures.
11. Toxicological information	
Influence to eye	Isocyanates may cause irritation with lacrimation and possibly conjunctivitis.
Influence to skin	Isocyanates may cause irritation with skin conditions ranging from Itching to widespread eczema. Allergic sensitization is possible, but only rarely.
Acute oral	No data available
Acute suction	No data available
Toxicity of generation	No data available
Chronic	No data available





12. Ecological Information				
Ecotoxicity	No data available			
Persistence and degradability	No data available			
Bioaccumulative potential	No data available			
Mobility in oil	No data available			
Other adverse effects	No data available			
13. Disposal Considerations				
Waste disposal regulation	Observe all federal, state, and local regulations when disposing of this substance.			
Waste disposal method				
. Packing & core	Destroy the product by incineration			
14. Transport Information				
UN number	No data available			
UN proper shipping name	Not applicable			
Transport hazard class	Not applicable			
Packing group(if applicable)	Not applicable			
Marin pollution	No data available			
15. Regulatory Information				
Industrial Safety and Health Act	No data available			
Toxic Chemical Control Act	No data available			
Dangerous Material Safety Control Act	No data available			
Waste Management Act	No data available			
Other requirements in domestic and other countries	Not applicable			
16. Other Information				
Information source and reference	Korea industrial safety cooperation, Mdl information system inc. Co. (u.s)			