

PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | F 800.294.0067 586.294.0067 | college-park.com



	FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE†	ENVIROSHIELD	HEEL HEIGHT	
VERT SHOCK	 FRESH WATER PROOF	AVIATOR	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm		6.5 in	979 g	3	L5987 PDAC APPROVED		0.38 in
TORSION + VERT SHOCK	 FRESH WATER PROOF	VOYAGER	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm		7.5 in	1,174 g	3	L5987 + L5984 PDAC APPROVED		0.38 in
INTEGRATED SPRING TECHNOLOGY	 SALT WATER PROOF	SOLEUS	Endo (4-hole)	220 lbs (21-24 cm) 250 lbs (25-26 cm) 275 lbs (27-30 cm)	21-30 cm		6.4 in (21-24 cm) 7.2 in (25-26 cm) 7.6 in (27-30 cm)	667 g	3	L5981 PDAC APPROVED		0.38 in
		VELOCITY	Endo (IP)	250 lbs (25-26 cm) 275 lbs (27-30 cm)	25-30 cm		4.7 in (25-26 cm) 5.2 in (27-30 cm)	631 g	3	L5981 + L5986		0.38 in
TRI-AXIAL	 FRESH WATER PROOF	TERRAIN	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm		3.4 in (21-25 cm) 3.6 in (26-30 cm)	815 g	3	L5981 + L5986 PDAC APPROVED		0.38 in
		VENTURE	Endo (IP) Exo (ALX)	250 lbs (21-24 cm) 275 lbs (25-30 cm)*	21-30 cm		2.5-2.7 in (IP) 5.0-5.2 in (ALX)	585 g	3	L5981 + L5986		0.38 in
		TRUSTEP	Endo (IP) Exo (ALX)	300 lbs (Endo) 352 lbs (Exo)	22-31 cm		3.5 in (IP) 6.0 in (ALX)	678 g	3 18mo / 300+ lbs	L5979 PDAC APPROVED		0.5 in
		TRIBUTE	Endo (IP)	220 lbs	21-30 cm		2.4 in	529 g	2	L5979 PDAC APPROVED		0.38 in
CARBON+ TORSION	 FRESH WATER PROOF	ORBIT	Endo (IP)	330 lbs	21-30 cm		3.7 in (21-25 cm) 3.9 in (26-30 cm)	895 g	3	L5981 + L5984 PDAC APPROVED		0.38 in
CARBON	 FRESH WATER PROOF	HORIZON HD	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm		2.3 in	559 g	3	L5981 PDAC APPROVED		0.38 in
CURVED HYDRAULIC		ODYSSEY _{K3}	Endo (IP)	275 lbs	21-30 cm		3.0 in	749 g	3	L5981 + L5968		0.38 in
		ODYSSEY _{K2}	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm		3.1 in (21-24 cm) 3.3 in (25-30 cm)	744 g	2	L5972 + L5968		0.38 in

* Low impact only

**26 cm, including
Enviroshell

Caucasian, Tan,
Brown, Jet Black

† The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | F 800.294.0067 586.294.0067 | college-park.com



	FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT*	WTY	L-CODE†	ENVIROSHELL	HEEL HEIGHT
K2		CELSUS	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	526 g	2	L5972 + L5986	 standard	0.38 in
		TEMPO	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	500 g	2	L5972	 standard	0.38 in
	 SALT WATER PROOF	BREEZE	Endo (IP)	220 lbs (21-25 cm) 275 (26-30 cm)	21-30 cm	 2.4 in (21-25 cm) 2.6 in (26-30 cm)	523 g (25 cm)	2	L5972	 standard	0.38 in
K2 VACUUM	 NEW!	CELSUS iVT	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	652 g	2	L5972 + L5986 + L5781	 standard	0.38 in
	 NEW!	TEMPO iVT	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	626 g	2	L5972 + L5781	 standard	0.38 in
ADJUSTABLE HEEL		ACCENT	Endo (IP) D.Pylon (DP)	220 lbs (21-24 cm) 250 lbs (25-28 cm)	21-28 cm	 3.3-3.9 in (IP) 7.8-8.0 in (4-H) 7.8-8.1 in (male) 8.3-8.5 in (female)	608 g (IP) 761 g (DP) w/pylon	2	L5981+ L5986+ L5990	 narrow & wide	2.0 in (range)
STUBBIES	 SALT WATER PROOF	SIDEKICKS	Endo (IP)	275 lbs	ONE SIZE	 2.3 in	422 g	2	L5972 + L5986	No Enviroshell	0 in
PEDIATRIC	 NEW! FRESH WATER PROOF	SCOUT	Lam Adapter Pyramid Receiver Exo (ALX)	55 lbs (13-15 cm) 100 lbs (16-18 cm) 132 lbs (19-22 cm)	13-22 cm	 1.9-2.1 in (Lam Adpt) 1.8-2.1 in (Pyramid) 2.1-2.4 in (Receiver) 4.1-4.3 in (ALX)	183-360**g	1	L5981 PDAC APPROVED	 standard	0.24 in (13-15cm) 0.25 in (16-18 cm) 0.38 in (19-22 cm)
		TRUPER	Endo (IP) Exo (ALX)	100 lbs (16-18 cm) 132 lbs (19-21 cm)	16-21 cm	 2.1-2.4 in (IP) 4.3-4.6 in (ALX)	215-314 g (16-21 cm)	1	L5979	 standard	0.25 in

*26 cm, including Enviroshell
**13-22 cm, including Pyramid Adapter and Enviroshell

Caucasian, Tan,
Brown

		KNEE	TYPE	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOME TO KNEE CENTER	FLEXION RANGE	L-CODE†	WTY
K2		GUARDIAN	Friction Brake	275 lbs	533 g	5.2 in	1.0 in	145°	L5812+ L5845+ L5850+ L5925	2
K3		VICTOR	Pneumatic	275 lbs	710 g	8 in	1.1 in	145°	L5822+L5845+L5850	2
K3 / K4	 FRESH WATER PROOF	CAPITAL	Hydraulic	330 lbs	1010 g (pylon) 1020 g (pyramid)	9 in	0.67 in	130°	L5828+L5845+L5850+L5925	3

† The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.