

F21 Maverick Xtreme AT

Product features

- Developed for extremely high loads
- Split keel design delivers +/- 16 degree inversion/eversion for all-terrain control
- Smooth rollover during stance phase
- Lightweight fiberglass
- Innovative heel / keel design
- Waterproof



Technical data

K-Level	3, 4
Max. body weight	365 lbs / 166 kg
Sizes	23-30 cm
Heel height	3/8" / 10 mm
Weight with footshell*	28.15 oz / 798 g
Build height*	6 11/16" / 170 mm

* Reference size is 26 cm.

F21 Maverick Xtreme AT

Order form

Customer		Shipping address (if different from customer address)	
Customer no.		Customer no.	
Company		Company	
Street		Street	
Postal code/city		Postal code/city	
O&P professional		Customer ref.	

Stiffness chart

Body weight	Activity level		
	Low	Moderate	High
100–115 lbs / 44–52 kg	1	1	2
116–130 lbs / 53–59 kg	1	2	3
131–150 lbs / 60–68 kg	2	3	4
151–170 lbs / 69–77 kg	3	4	5
171–195 lbs / 78–88 kg	4	5	6
196–220 lbs / 89–100 kg	5	6	7
221–255 lbs / 101–116 kg	6	7	8
256–285 lbs / 117–130 kg	7	8	9
286–325 lbs / 131–147 kg	8	9	–
326–365 lbs / 148–166 kg	9	–	–

Scope of delivery

- F21* Maverick Xtreme AT
- KIT-00-114* Set of heel wedges
- S0-NPS-200* Spectra protective sock black

Accessories & spare parts

- S0-NPS-100* Spectra protective sock white
- ACC-00-10300-00 Footshell removal tool

Available footshell variants

- FTC-3A-1*: Footshell Maverick standard (without cap)
- FTC-2A-1*-S*: Footshell Maverick sandal toe - available in size 23-28 cm

Foot module part number

Reference number	Stiffness	Size	Toe Configuration
F21 - 00 - 0	A	-	-
	Stiffness	Size (cm)	Toe Configuration
	1–9	23, 24, ..., 30	RU Regular toe, universal SL Sandal toe, left SR Sandal toe, right

Footshell part number

Reference number	Generation	Size	Color	Toe	Side
FTC - A - 1	4	-	-	-	-
	Generation	Size (cm)	Color	Toe	Side
	2 Sandal toe	23, 24, ..., 30	L Light	R Regular	L Left
	3 Standard		M Medium	S Sandal	R Right
			D Dark		