

VS4 Kintrol

Product features

- Hydraulic prosthetic foot
- Full fiberglass keel for optimal flexibility and comfort
- 12° range of motion (2° DF, 10° PF): Increased ankle movement for a more natural gait
- The active dorsi-assist spring aides in toe clearance during swing phase to help prevent toe stubbing and tripping
- Heel stiffness can be adjusted easily with U-shaped bumpers designed to enhance balance and provide stability



Technical data

K-Level	2
Max. body weight	300 lbs / 136 kg
Sizes	23-30 cm
Heel height	3/8" / 10 mm
Weight with footshell*	33.62 oz / 953 g
Build height*	4 7/16" / 112 mm

* Reference size is 26 cm.

MPK combination



VS4 Kintrol

Order form

Customer		Shipping address (if different from customer address)	
Customer no.		Customer no.	
Company		Company	
Street		Street	
Postal code/city		Postal code/city	
O&P professional		Customer ref.	

Stiffness chart

Body weight	Stiffness
100–130 lbs / 45–59 kg	1
131–180 lbs / 60–81 kg	2
181–240 lbs / 82–109 kg	3
241–300 lbs / 110–136 kg	4

Scope of delivery

- VS4* Kintrol
- KIT-00-114* Set of heel wedges
- S0-NPS-200* Spectra protective sock black

Accessories & spare parts

- S0-NPS-100* Spectra protective sock white
- ACC-00-10300-00 Footshell removal tool

Foot module part number

Reference number	Stiffness	Size	Toe Configuration
VS4 - 00 - 0	A		
	Stiffness	Size (cm)	Toe Configuration
	1–4	23, 24, ..., 30	RU Regular toe, universal SL Sandal toe, left SR Sandal toe, right

Available footshell variants

- FTC-3B-1*: Footshell K2 standard (without cap)
- FTC-2B-1*-S*: Footshell K2 sandal toe (without cap) – available in size 23-28 cm

Footshell part number

Reference number	Generation	Size	Color	Toe	Side
FTC - B - 1				4 -	
	Generation	Size (cm)	Color	Toe	Side
	2 Sandal toe	23, 24, ..., 30	L Light	R Regular	L Left
	3 Standard		M Medium	S Sandal	R Right
			D Dark		