



The Camber Axis Hinge® was developed by David J. Hoy, CPO to provide an adjustable ROM ankle joint with anatomical axis alignment for use in thermoplastic orthoses. Equipped with seven different color coded ROM keys (0° stop pictured above), the Camber Axis Hinge® eliminates the need for posterior stop mechanisms. This ankle joint permits solid ankle or variable anterior/posterior stop settings. Manufactured of 410 stainless steel for strength and durability. From Becker Orthopedic.

PCE Credits!

Camber Axis Hinge Information CD is available for self-study and PCE credits. Call for yours today.

Camber Axis	Hinge Kit					
Order No.	Size	Patient Weigh	t Width	He	eight	
750-S	Small	80-100 lbs	1-1/8" (29	mm) 3-1/8"	(79mm)	
750-M	Medium	< 160 lbs	1-1/2" (38	mm) 3-3/4"	(95mm)	
750-L	Large	< 220 lbs	1-9/16" (40	mm) 4-1/2"	(114mm)	
Replacement	t Parts Kit Cor	mplete				
Small	Medium	Large				Description
750R-S	750R-M	750R-L				Replacement Parts Kit
Individual Re	eplacement Co	omponents				
Small	Medium	Large				Description
750-1-S	750-1-M	750-1-L				Camber Axis Proximal Jt
750-2-S	750-2-M	750-2-L				Camber Axis Distal Joint
750-3-S	750-3-L/M	750-3-L/M				Pivot Screw
750-4	750-4	750-4				8-32 Screw for Stop
750-5-S	750-5-L/M	750-5-L/M				SS Washer for Pivot Screw
750-6-S	750-6-M	750-6-L				Plastic Friction Washer
750-14	750-15	750-16				Aliplast Pads, PR
750-14A	750-15A	750-16A				Adhesive Backed Pads, PF
Individual Re	eplacement R	OM Keys				
SM Left	SM Right	MD Left	MD Right	LG Left	LG Right	Description
750-7-S-L	750-7-S-R	750-7-L/M-L	750-7-L/M-R	750-7-L/M-L	750-7-L/M-R	0° Stop (Silver)
750-8-S-L	750-8-S-R	750-8-L/M-L	750-8-L/M-R	750-8-L/M-L	750-8-L/M-R	5° Stop (Red
750-9-S-L	750-9-S-R	750-9-L/M-L	750-9-L/M-R	750-9-L/M-L	750-9-L/M-R	10° Stop (Blue)
750-10-S-L	750-10-S-R	750-10-L/M-L	750-10-L/M-R	750-10-L/M-L	750-10-L/M-R	15° Stop (Purple)
750-11-S-L	750-11-S-R	750-11-L/M-L	750-11-L/M-R	750-11-L/M-L	750-11-L/M-R	0°-30° Stop (Green)
750-12-S-L	750-12-S-R	750-12-L/M-L	750-12-L/M-R	750-12-L/M-L	750-12-L/M-R	5°-10° Stop (Black)
750-13-S-L	750-13-S-R	750-13-L/M-L	750-13-L/M-R	750-13-L/M-L	750-13-L/M-R	7.5°-10° Stop (Yel.)