

# MODULAR COMPONENTS

## EZ Adapt Series



### 1702T, 1703T, 1704T, 1705T, 1725T EZ ADAPT SERIES

EZ ADAPT components provide versatility to shift and/or rotate as needed, bringing easy solutions to prosthetic alignment needs without adding significant weight or modifying the prosthetic socket.

**Warranty:** 2 year

P/N	Description	Weight Limit
① 1702T	Rotating Receiver, 45mm, Ti	136kg / 300lbs
② 1703T	Rotating Receiver, 60mm, Ti	136kg / 300lbs
③ 1704T	Offset Rotating Receiver, Ti	136kg / 300lbs
④ 1705T	Rotating Receiver Clamp, Ti	136kg / 300lbs
⑤ 1725T	Offset Rotating Pyramid, Ti	136kg / 300lbs
⑥ 1713T	15 Degrees Angled Offset Receiver	136kg / 300lbs
⑦ 1723T	7.5 Degrees Angled Offset Receiver	136kg / 300lbs

Torque Value	Torque (Nm)	Hex (mm)
M8 Set Screw	15 Nm	4mm wrench
M6 Cap Screw	10 Nm	5mm wrench



### 1216 ROTATING RECEIVER

The Rotating Pyramid Receiver can be used with 1214T or 1221S. The 1216T is forged and machined for high strength and quality.

**Warranty:** 2 year

P/N	Material	Product Weight	Weight Limit
⑧ 1216T	Titanium	48g	136kg / 300lbs
1216S	Stainless Steel	68g	125kg / 275lbs

Torque Value	Torque (Nm)	Hex (mm)
M8 Set Screw	15 Nm	4mm wrench

**TO ORDER CALL:** 714-524-0663 / **FAX:** 714-364-8113



## EZ Adapt Series

**1737T, 1727T, 1717T, 1718T, 1751T**

**EZ ADAPT SERIES**

**Warranty:** 2 year

①



②



③



P/N	Description	Weight Limit
① 1737T	Extreme linear offset 4-hole pyramid (provides up to 20mm of offset)	100kg / 220lbs
② 1727T	Diagonal offset 4-hole pyramid (provides up to 12mm of offset)	100kg / 220lbs
③ 1717T	Linear offset 4-hole pyramid (provides up to 7mm of offset)	100kg / 220lbs
④ 1718T	Sliding 4-hole receiver (12mm maximum slide distance)	100kg / 220lbs
⑤ 1751T	Variable Height Double Ended Adapter (Build Height range 59mm to 72mm)	100kg / 220lbs

Torque Value	Torque (Nm)	Hex (mm)
M8 Set Screw	15 Nm	4mm wrench
Sliding Adjustment M6 Set Screw	5 Nm	3mm wrench
M5 Cap Screw	7 Nm	4mm wrench

④



⑤





## Double Ended Sliding Adapter

### 1229

#### DOUBLE ENDED SLIDING ADAPTER



The Double Ended Sliding Adapter permits additional sliding adjustment of up to 13mm between the prosthetic socket and pyramid adapter, even as the prosthesis is being worn. The sliding adjustment allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid.

**Warranty:** 2 year

P/N	Material	Height	Product Weight	Weight Limit
1229T	Titanium	60mm	55g	125kg / 275lbs
1229S	Stainless Steel	60mm	100g	125kg / 275lbs

Torque Value	Torque (Nm)	Hex (mm)
M8 Set Screw	15 Nm	4mm wrench

### 1228

#### DOUBLE ENDED SLIDING ADAPTER WITH PYRAMID



The Double Ended Sliding Adapter with Pyramid permits additional sliding adjustment of up to 13mm between the prosthetic socket and pyramid adapter, even as the prosthesis is being worn. The sliding adjustment allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid.

**Warranty:** 2 year

P/N	Material	Height	Product Weight	Weight Limit
1228T	Titanium	60mm	48g	125kg / 275lbs
1228S	Stainless Steel	60mm	83g	125kg / 275lbs

Torque Value	Torque (Nm)	Hex (mm)
M8 Set Screw	15 Nm	4mm wrench
M6 Cap Screw	10 Nm	5mm wrench
Sliding Adjustment M6 Set Screw	5 Nm	3mm wrench



## Tube Clamps



Offset = 1/2 inch

### 1219

#### SLIDING TUBE CLAMP

The titanium 30mm sliding tube clamp adapter permits additional sliding adjustment between the prosthetic socket and tube adapter, even as the prosthesis is being worn. The sliding adjustment allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid.

**Warranty:** 2 year

P/N	Material	Product Weight	Weight Limit
1219T	Titanium	185g	100kg / 220lbs

Torque Value	Torque (Nm)	Hex (mm)
M5 Cap Screw	7 Nm	4mm wrench
M8 Set Screw (Alignment Adjustment Screw)	10 Nm	4mm wrench



### 1252

#### TUBE CLAMP WITH PYRAMID

##### Titanium Tube Clamp with Pyramid

The titanium 30mm tube adapter with pyramid is designed for an optional strength while maintaining low weight. High strength titanium provides high quality and strong product.

**Warranty:** 2 year

##### Stainless Steel Tube Clamp with Pyramid

The stainless steel 30mm tube clamp with pyramid is made of high strength stainless steel alloys providing a strong and durable component.

**Warranty:** 2 year

P/N	Material	Product Weight	Weight Limit
1252T	Titanium	98g	100kg / 220lbs
1252S	Stainless Steel	105g	100kg / 220lbs

Torque Value	Torque (Nm)	Hex (mm)
M5 Cap Screw	7 Nm	4mm wrench