



## Green Dot Total Contact Suction Socket Valve

- Reliable seal
- Lightweight design

**Indications:** Transfemoral amputees who use thermoformed sockets

### Selection

Model No.	Description
P12-310-1000	Green Dot Total Contact Suction Socket Valve, Plastic, Manual Expulsion
T15-600-0000	Valve Key for Green Dot Valves



## Green Dot SFS Valve

- Lightweight, replaceable valve housing
- Reliable seal
- Lightweight design

**Indications:** Transfemoral amputees who use thermoformed sockets

### Selection

Model No.	Description
P12-340-1000	Green Dot SFS Valve, Plastic, Manual Expulsion
T15-600-0000	Valve Key for Green Dot Valves



## Green Dot Total Contact Suction Valve

- Industry standard in reliable suction
- Lightweight design

**Indications:** Transfemoral amputees who use lamination sockets

### Selection

Model No.	Description
P12-320-1000	Green Dot Total Contact Suction Valve, Stainless Steel, Manual Expulsion
T15-600-0000	Valve Key for Green Dot Valves

### Specifications

(All Green Dot Valves)

Distal End of Valve to Top of Threads	10.8 mm / 0.4 in
Diameter at Valve Base	22 mm / 0.9 in
Warranty	2 years
Includes	Valve Key, Valve Plug, Flat Washer, Screw
Made in USA	



## Below Knee Valve

- Self expulsion valve
- Installed at the distal end of socket
- For use with suction suspension

**Indications:** Transtibial amputees

### Selection

Model No.	Description
P36110	Below Knee Valve

### Specifications

Minimum Distal Socket Thickness	19 mm / 0.8 in
Warranty	2 years
Made in USA	